



Product Description

GAO's V.27ter software implements the ITU V.27ter recommendation. It uses a data signaling rate of 4800 bps with eight phases differentially encoded modulation and operates at a reduced rate of 2400 bps with four phase differentially encoded modulation.

Key Features

- ✓ Optional backward channel at modulation rates of up to 75 symbols per second.
- ✓ Modulation occurs at 1800Hz.
- ✓ Transmitted power levels conform to V.2.
- ✓ Modulation rate is 1200 or 1600 symbols.
- ✓ It consists of transmitting functions and receiving functions which are called to transmit and receive bits in groups of 2 to 3 (referred to as symbols) at a rate of 1200 or 1600 symbols per second respectively.
- ✓ Highly optimized in C and multi-channel ready.

Leadership in Embedded Communications Software

With over a decade of experience, GAO leads the embedded communications software market by providing comprehensive modem, fax, speech, and telephony technologies; broad technical expertise; and unsurpassed support to our world-class customers including electronics, communications, and semiconductor companies across the globe. GAO's software integrates easily with MP3, MPEG, TCP/IP, and most popular real-time operating systems.



Rigorous Testing

GAO's testing facilities are equipped with state-of-the-art test equipment. Our software is rigorously tested on TAS, Consultronics, Rochelle, Advent and Telegra equipment under various channel models according to the relevant ITU or TIA standards. All GAO's speech software has passed the test vectors specified by the ITU. Our telephony software meets all appropriate TIA, EIA, BellCore, and Mitel standards.

GAO Group

Celebrating Over 15 Years of Innovation

GAOResearch.com

GAOTek.com

GAOComm.com

GAOInstruments.com

GAORFID.com

GAORFIDAssetTracking.com

GAOFiberOptics.com

GAOEmbedded.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Ext. 206 for Sales

sales@gaoresearch.com